



Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

I Identification of the hazardous chemical and of the supplier

- · Product identifier
- · Trade name: Transpoxy MIO Primer Part B
- · Article number: 1.65 (B)
- · Recommended use of the chemical and restrictions on use No further relevant information available.
- · Application of the substance / the mixture Coating material
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

KOSSAN PAINT (M) SDN. BHD.

1,Jalan Koporat 1/KU9, Taman

Perindustrian Meru, 42200 Kapar,

Selangor Darul Ehsan, Malaysia.

Further information obtainable from:

Product safety department. lsk@kossanpaint.com.my

· Emergency telephone number:

Manufacturer/supplier

603-33922799

2 Hazard identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapour.



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS05
- · Signal word Danger
- · Hazard-determining components of labelling:

xylene

iso-butanol

butan-1-ol

· Hazard statements

Flammable liquid and vapour.

(Contd. on page 2)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy MIO Primer Part B

(Contd. of page 1)

Causes skin irritation.

Causes serious eye damage.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous	· Dangerous components:			
1330-20-7	xylene	≥10-<35%		
	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315			
78-83-1	iso-butanol	≥10-<15%		
	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336			
71-36-3	butan-1-ol	≥1-<2.2%		
	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336			
112-24-3	3,6-diazaoctanethylenediamin	<i>≥</i> 0.1-<0.8%		
	Skin Corr. 1, H314; • Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412			

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy MIO Primer Part B

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy MIO Primer Part B

(Contd. of page 3)

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-83-1 iso-butanol (≥10-<15%)

PEL (Malaysia) Long-term value: 152 mg/m³, 50 ppm

71-36-3 butan-1-ol (≥1-<2.2%)

PEL (Malaysia) Ceiling limit: 152 mg/m³, 50 ppm

(kulit)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Colour: Amber Clear
Odour: Characteristic

(Contd. on page 5)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy MIO Primer Part B

	(Contd. of page 4
· Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point Initial boiling point and boiling rang	Undetermined. e 140°C
Flash point:	25 °C
· Flammability (solid, gas)	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure:	Not determined.
Density at 20°C: Relative density Vapour density Evaporation rate	0.9 g/cm³ Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

M

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy MIO Primer Part B

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for co	lassification:
----------------------------------	----------------

1330-20-7 xylene

 Oral
 LD50
 4,300 mg/kg (rat)

 Dermal
 LD50
 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion or irritation Irritant to skin and mucous membranes.
- · Serious eye damage or eye irritation Strong irritant with the danger of severe eye injury.
- · Respiratory / skin sensitization No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal information

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14 Transportation information

- · UN-Number
- · ADR, IMDG, IATA

UN1263

(Contd. on page 7)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy MIO Primer Part B

	(Contd. of page 6)
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· Transport hazard class(es) · ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· Packing group · ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
· Special precautions for user · EMS Number:	Warning: Flammable liquids. F-E, <u>S-E</u>

15 Regulatory information

· UN "Model Regulation":

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · EHS reference list

and the IBC Code

All ingredients are listed.

• GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Not applicable.

UN 1263 PAINT, 3, III

- · Hazard pictograms GHS02, GHS05
- · Signal word Danger
- · Hazard-determining components of labelling:

· Transport in bulk according to Annex II of Marpol

xylene

iso-butanol

butan-1-ol

· Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces - No smoking.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 8)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy MIO Primer Part B

(Contd. of page 7)

- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department.
- · Contact: Mr. S.K. Lim
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Corr. 1: Skin corrosion or irritation – Category 1

Skin Irrit. 2: Skin corrosion or irritation – Category 2

Eye Dam. 1: Serious eye damage or eye irritation - Category 1

Skin Sens. 1: Skin sensitization – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - chronic hazard - Category 3

* * Data compared to the previous version altered.

MY