



Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

I Identification of the hazardous chemical and of the supplier

- · Product identifier
- · Trade name: Transpoxy Sealer 1.99 Part B
- · Article number: 1.99 (B)
- Recommended use of the chemical and restrictions on use No further relevant information available.
- · Application of the substance / the mixture Coating material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

KOSSAN PAINT (M) SDN. BHD.

1,Jalan Koporat 1/KU9, Taman

Perindustrian Meru, 42200 Kapar,

Selangor Darul Ehsan, Malaysia.

Further information obtainable from:

Product safety department. lsk@kossanpaint.com.my

Emergency telephone number:

Manufacturer/supplier

603-33922799

2 Hazard identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Haz. H304 May be fatal if swallowed and enters airways.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H312 Harmful if in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy Sealer 1.99 Part B

(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS05, GHS07, GHS08
- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapour.

Harmful if in contact with skin or inhaled.

Causes skin irritation.

Causes serious eye damage.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific measures (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

108-88-3 toluene

🅸 Flam. Liq. 2, H225; 🗞 Repr. 2, H361; STOT RE 2, H373; Asp. Haz., H304; 💠 Skin

Irrit. 2, H315; STOT SE 3, H336

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Call for a doctor immediately.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

≥20-<70%

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy Sealer 1.99 Part B

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy Sealer 1.99 Part B

(Contd. of page 3)

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene (≥20-<70%)

PEL (Malaysia) Long-term value: 188 mg/m³, 50 ppm

(kulit)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colour: Clear

· Odour: Characteristic
· Odour threshold: Not determined.

(Contd. on page 5)

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy Sealer 1.99 Part B

	(Contd. of page 4
· pH-value:	Not determined.
Change in condition Melting point/freezing point Initial boiling point and boiling rang	Undetermined. re 110°C
Flash point:	5 °C
· Flammability (solid, gas)	Not applicable.
Ignition temperature:	535 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits: Lower: Upper:	1.2 Vol % 7 Vol %
Vapour pressure:	Not determined.
Density: Relative density Vapour density Evaporation rate	Not determined. Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

M

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy Sealer 1.99 Part B

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values re	levant for	classi	fication:
---------------------	------------	--------	-----------

108-88-3 toluene		
	LD50	5,000 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat) 12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- Primary irritant effect:
- · Skin corrosion or irritation Irritant to skin and mucous membranes.
- · Serious eye damage or eye irritation Irritating effect.
- · Respiratory / skin sensitization No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal information

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

MV

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy Sealer 1.99 Part B

(Contd. of page 6)

TINI NI I		
UN-Number	UN1263	
ADR, IMDG, IATA	U1V1 203	
UN proper shipping name	Jacob (IVIII	
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
ADR, IMDG, IATA		
Class	3 Flammahla liquids	
	3 Flammable liquids. 3	
Label	J	
Packing group		
ADR, IMDG, IATA	III	
Environmental hazards:		
Marine pollutant:	No	
marine pountant.	ш : гі 11 1: :1	
	Warning: Flammable liquids.	
Special precautions for user	Warning: Flammable liquids. F-E, <u>S-E</u>	
Special precautions for user EMS Number:	F-E, <u>S-E</u>	
Special precautions for user EMS Number: Transport in bulk according to Annex I and the IBC Code	F-E, <u>S-E</u>	

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

• EHS reference list 108-88-3 toluene

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS05, GHS07, GHS08
- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapour.

Harmful if in contact with skin or inhaled.

Causes skin irritation.

Causes serious eye damage.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Somme rinsing.

Printing date 19.04.2021 Version number 1 Revision: 19.04.2021

Trade name: Transpoxy Sealer 1.99 Part B

(Contd. of page 7)

Specific measures (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department.
- · Contact: Mr. S.K. Lim
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Irrit. 2: Skin corrosion or irritation – Category 2

Eye Dam. 1: Serious eye damage or eye irritation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Haz.: Aspiration hazard - Category 1

* * Data compared to the previous version altered.

MY