

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

1 Identification of the hazardous chemical and of the supplier

- **Product identifier**
- **Trade name:** Transpoxy Tar KPC-210 Part B
- **Article number:** KPC-210 (B)
- **Recommended use of the chemical and restrictions on use** No further relevant information available.
- **Application of the substance / the mixture** Coating material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
KOSSAN PAINT (M) SDN. BHD.
1, Jalan Koporat 1/KU9, Taman
Perindustrian Meru, 42200 Kapar,
Selangor Darul Ehsan, Malaysia.
- **Further information obtainable from:**
Product safety department.
lsk@kossanpaint.com.my
- **Emergency telephone number:**
Manufacturer/supplier
603-33922799

2 Hazard identification

- **Classification of the substance or mixture**



flame

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
--------------	------	-------------------------------------



health hazard

Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Haz.	H304	May be fatal if swallowed and enters airways.



corrosion

Skin Corr. 1	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.



environment

Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.
-------------------	------	--

(Contd. on page 2)

MY

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy Tar KPC-210 Part B

(Contd. of page 1)



Skin Sens. 1 H317 May cause allergic skin reaction.
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms** GHS02, GHS05, GHS07, GHS08, GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

iso-butanol

2,2'-iminodiethylamine

toluene

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

· **Hazard statements**

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

May cause allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Specific treatment (see on this label).

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

108-88-3	toluene	$\geq 20 - < 30\%$
	Flam. Liq. 2, H225; Repr. 2, H361; STOT RE 2, H373; Asp. Haz., H304; Skin Irrit. 2, H315; STOT SE 3, H336	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	$\geq 25 - < 30\%$
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
78-83-1	iso-butanol	$\geq 20 - < 30\%$
	Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	

(Contd. on page 3)

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy Tar KPC-210 Part B

(Contd. of page 2)

111-40-0	2,2'-iminodiethylamine	≥5-<16%
	⚠ Skin Corr. 1, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Call for a doctor immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

MY

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: **Transpoxy Tar KPC-210 Part B**

(Contd. of page 3)

Prevent formation of aerosols.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep container tightly sealed.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

108-88-3 toluene (≥20-<30%)

PEL (Malaysia)	Long-term value: 188 mg/m ³ , 50 ppm (kulit)
----------------	--

78-83-1 iso-butanol (≥20-<30%)

PEL (Malaysia)	Long-term value: 152 mg/m ³ , 50 ppm
----------------	---

111-40-0 2,2'-iminodiethylamine (≥5-<16%)

PEL (Malaysia)	Long-term value: 4.2 mg/m ³ , 1 ppm (kulit)
----------------	---

- **Additional information:** The lists valid during the making were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy Tar KPC-210 Part B

(Contd. of page 4)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Colour:

Amber Clear

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/freezing point

Undetermined.

Initial boiling point and boiling range

Undetermined.

· **Flash point:**

5 °C

· **Flammability (solid, gas)**

Not applicable.

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:

1 Vol %

Upper:

12 Vol %

· **Vapour pressure at 20 °C:**

29 hPa

· **Density at 20 °C:**

0.92 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water**

Not determined.

· **Viscosity:**

Dynamic:

Not determined.

Kinematic:

Not determined.

(Contd. on page 6)

MY

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: **Transpoxy Tar KPC-210 Part B**

(Contd. of page 5)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:****108-88-3 toluene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

111-40-0 2,2'-iminodiethylamine

Oral	LD50	1,080 mg/kg (rat)
Dermal	LD50	1,090 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion or irritation** Irritant to skin and mucous membranes.
- **Serious eye damage or eye irritation** Irritating effect.
- **Respiratory / skin sensitization** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

-MY-

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy Tar KPC-210 Part B

(Contd. of page 6)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal information

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transportation information

- | | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · ADR, IMDG, IATA | UN1263 |
| <ul style="list-style-type: none"> · UN proper shipping name · ADR · IMDG, IATA | 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
PAINT |
| <ul style="list-style-type: none"> · Transport hazard class(es) · ADR | <div style="display: flex; align-items: center; justify-content: center;">   </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids.
3 |
| <ul style="list-style-type: none"> · IMDG, IATA | <div style="display: flex; align-items: center; justify-content: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids.
3 |
| <ul style="list-style-type: none"> · Packing group · ADR, IMDG, IATA | III |
| <ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: · Special marking (ADR): | Product contains environmentally hazardous substances:
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin
(number average molecular weight ≤ 700)
No
Symbol (fish and tree) |
| <ul style="list-style-type: none"> · Special precautions for user · EMS Number: | Warning: Flammable liquids.
F-E, <u>S-E</u> |

(Contd. on page 8)

-MY-

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: **Transpoxy Tar KPC-210 Part B**

(Contd. of page 7)

· **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **EHS reference list**

All ingredients are listed.

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms** GHS02, GHS05, GHS07, GHS08, GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

iso-butanol

2,2'-iminodiethylamine

toluene

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

· **Hazard statements**

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

May cause allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Specific treatment (see on this label).

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department.

(Contd. on page 9)

MY

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 28.04.2021

Version number 1

Revision: 28.04.2021

Trade name: Transpoxy Tar KPC-210 Part B

(Contd. of page 8)

· **Contact:** Mr. S.K. Lim

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1: Skin corrosion or irritation – Category 1

Skin Irrit. 2: Skin corrosion or irritation – Category 2

Eye Dam. 1: Serious eye damage or eye irritation – Category 1

Eye Irrit. 2: Serious eye damage or eye irritation – Category 2

Skin Sens. 1: Skin sensitization – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Haz.: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - chronic hazard – Category 2

· *** Data compared to the previous version altered.**

MY