

Safety Data Sheet

according to P.U.(A) 310/2013

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

1 Identification of the hazardous chemical and of the supplier

· Product identifier

· Trade name: Transpoxy HB MIO KPC-945 Part A

- · Article number: KPC-945 (A)
- **Recommended use of the chemical and restrictions on use** No further relevant information available.
- · Application of the substance / the mixture Coating material
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: KOSSAN PAINT (M) SDN. BHD. 1,Jalan Koporat 1/KU9, Taman Perindustrian Meru, 42200 Kapar, Selangor Darul Ehsan, Malaysia.
- Further information obtainable from: Product safety department.
 lsk@kossanpaint.com.my
 Emergency telephone number:
- Manufacturer/supplier 603-33922799

2 Hazard identification

· Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· Label elements

- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms GHS02, GHS07
- · Signal word Warning
- · Hazard statements
- Flammable liquid and vapour.
- Harmful if swallowed.
- Causes skin irritation.
- Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

MY

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

Trade name: Transpoxy HB MIO KPC-945 Part A

(Contd. of page 1)

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

3 Composition and information of the ingredients of the hazardous chemical

· Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
1330-20-7	xylene	<6.5%	
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
107-98-2	monopropylene glycol methyl ether	<i>≤</i> 2.2%	
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 3, H331; 🚸 STOT SE 3, H336		
108-38-3	m-xylene	<i>≤</i> 2.2%	
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
Additional information: For the wording of the listed hazard phrases refer to section 16.			

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Call for a doctor immediately.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

Trade name: Transpoxy HB MIO KPC-945 Part A

(Contd. of page 2)

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 monopropylene glycol methyl ether

PEL (Malaysia) Long-term value: 369 mg/m³, 100 ppm

108-38-3 m-xylene

PEL (Malaysia) Long-term value: 434 mg/m³, 100 ppm

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 4)

[•] MY

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

(Contd. of page 3)

Trade name: Transpoxy HB MIO KPC-945 Part A

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and cher General Information	nical properties
Appearance:	
Form:	Liquid
Colour:	Dark Grey / Silver Grey
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point Initial boiling point and boiling range	Undetermined. 2 Undetermined.
Flash point:	30 °C
Flammability (solid, gas)	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

Trade name: Transpoxy HB MIO KPC-945 Part A

	(Contd. of page
· Vapour pressure:	Not determined.
Density at 20 °C:	2.02 g/cm^3
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Solids content:	88.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion or irritation Irritant to skin and mucous membranes.
- · Serious eye damage or eye irritation Irritating effect.
- · Respiratory / skin sensitization No sensitising effects known.

• Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

(Contd. on page 6)

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

Trade name: Transpoxy HB MIO KPC-945 Part A

(Contd. of page 5)

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal information

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

UN-Number ADR, IMDG, IATA	UN1263	
UN proper shipping name		
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
Class	3 Flammable liquids.	
Label	3 Flammable liquids. 3	
Label Packing group		
Class Label Packing group ADR, IMDG, IATA Environmental hazards:	3	

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

Trade name: Transpoxy HB MIO KPC-945 Part A

		(Contd. of page 6)			
• EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>				
· Transport in bulk according to Annex II of Marpol					
and the IBC Code	Not applicable.				
· UN "Model Regulation":	UN 1263 PAINT, 3, III				

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· EHS reference list

1330-20-7 xylene

107-98-2 monopropylene glycol methyl ether

108-38-3 m-xylene

- *GHS label elements* The product is classified and labelled according to the Globally Harmonised System (GHS). • *Hazard pictograms* GHS02, GHS07
- Signal word Warning
- · Hazard statements

Flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. Causes serious eve irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces – No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Product safety department.
- · Contact: Mr. S.K. Lim

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 8)

Printing date 30.04.2021

Version number 1

Revision: 30.04.2021

Trade name: Transpoxy HB MIO KPC-945 Part A

(Contd. of page 7)

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - oral – Category 4 Acute Tox. 3: Acute toxicity - oral – Category 3 Skin Irrit. 2: Skin corrosion or irritation – Category 2 Eye Irrit. 2: Serious eye damage or eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3