



PRODUCT DATA SHEET

KOSELASTEX KET-SERIES

KOSELASTEX KET-SERIES

Non Aggregate Latex Texture paint

DESCRIPTION

KOSELASTEX is a high quality non aggregates Acrylic latex texture paint specially formulated to provide a uniform textured appearance to rough and irregular surfaces using common paint application tools. KOSELASTEX could be top coated with any emulsion colour paint or metallic effect paint such as KOSTALLIC PEARL series to provide an elegant and luxurious decorative finishing. It is also provide good crack resistance properties when high thickness of coating applied. No matter which technique you choose, KOSELASTEX will give you professional results with do-it-yourself simplicity.

AREA OF APPLICATION

KOSELASTEX is highly recommended for interior decorations of surfaces like concrete, plaster, gypsum, interior drywall, ceiling or drywall, design board, feature walls etc. KOSELASTEX particularly suitable for application on representative wall surfaces, e.g. shopping centers, office or residential buildings, hotels, restaurant or bistro, and residential area such as living room, bedroom etc

PHYSICAL PROPERTIES

Colour	: White or variety of colors choices.
Specific Gravity	: $1.44 \pm 0.03 \text{ gm/cm}^3$
Volume Solid	: $50 \pm 2\%$ (Depend on color)
Finish	: Matt
Open time / workability	: 30 - 40 minutes (depends on temperature and humidity).
Handling time	: 8 to 16 hours (Depend on temperature, humidity and thickness coating layer.
Flash Point	: Non-flammable

KOSSAN PAINT (M) SDN.BHD

1 Jalan Koporat 1/KU 9, Taman Perindustrian Meru, 42200 Kapar, Selangor D.E. Malaysia
Tel: 603-33922799; Fax: 603-33923799; e-mail: lsk@kossanpaint.com.my; Website: www.kossanpaint.com



PRODUCT DATA SHEET

KOSELASTEX KET-SERIES

SURFACE PREPARATION

It is essential to have a properly prepare surface to ensure precise and long lasting coating performance. Surface must be dry, clean, and free from any loose material, dirt, grease and other contaminants.

- ❑ **Powdery Wall**
High pressured water jetting (approx. 1500 psi) to clean the affected surfaces, allow drying thoroughly then applying 1-2 coats of Ultra-Seal basecoat.
- ❑ **Flaking / Peeling**
High pressured water jetting to removed affected surface, allow to dry prior to painting
- ❑ **Algae & Fungus Infested**
High pressured water jetting to removed all algae & fungus, than flash the surface with Kossan Fungicidal washes and allow surface to dry prior to painting.
- ❑ **Damp Surfaces**
To avoid from premature paint failure, surface to be painted must first be dry thoroughly prior to painting. It is important to find-out the source of dampness and repair with appropriate steps to stop dampness.

MIXING / METHOD OF APPLICATION

The product should be stirred thoroughly before and during application. Apply with paint brush, roller or special paint application tools to create different desired texture effect. Follow the specific technique instructions in the KOSELASTEX Texture Paint guide. Once the texture has dried, to change color or increase paint durability, apply 1 -2 coats of KOSSAN Interior or Exterior latex emulsion topcoat; especially topcoat with variety of KOSTALLIC PEARL colors in exotic appearance provide an aesthetic appearance.

KOSSAN PAINT (M) SDN.BHD

1 Jalan Koporat 1/KU 9, Taman Perindustrian Meru, 42200 Kapar, Selangor D.E. Malaysia
Tel: 603-33922799; Fax: 603-33923799; e-mail: lsk@kossanpaint.com.my; Website: www.kossanpaint.com



PRODUCT DATA SHEET

KOSELASTEX KET-SERIES

RECOMMENDED SYSTEM (*Metallic effect finishing*)

- Apply one coat of ULTRA-SEAL (White), diluted with 5% water, by using roller and allow it to dry.
- Apply one thick coat of KOSELASTEX TEXTURE COAT to create desired texture pattern with variety of paint application tools.
- Apply one coat of common latex emulsion color topcoat / basecoat (closer to the shade of KOSTALLIC PEARL) by using roller and allow it to dry.
- Apply first coat of the chosen color of undiluted KOSTALLIC PEARL, by using roller and allow it to dry.
- Repeat the same method for second coat of KOSTALLIC PEARL is necessary. Allow it to dry.

CONDITIONS

Humidity: below 90% R.H.

The temperature of the substrate should be minimum 15°C and at least 3°C above the dew point of the air, temperature and relative humidity measured in the vicinity of the substrate. The coating should not be exposed to oil, chemicals or mechanical stress until fully cured.

THEORETICAL COVERAGE & PACKING SIZE

Theoretical Coverage : Approx. 1 to 2 m²/kg per coat depends on porosity of the substrate and the thickness of the paint texture layer.

Packing Size : 5 litres & 18 litres

STORAGE

KOSELASTEX KET-SERIES have a minimum self-life of 12 months at cool and dry place. Containers must be kept tightly closed.

HEALTHY & SAFETY

Avoid skin and eyes contact by wearing suitable overalls, gloves, goggles, etc. Spillage on the skin should immediately be removed by thorough washing with water and soap. Eyes should be well flushed with water and medical attention sought immediately.

KOSSAN PAINT (M) SDN.BHD

1 Jalan Koporat 1/KU 9, Taman Perindustrian Meru, 42200 Kapar, Selangor D.E. Malaysia
Tel: 603-33922799; Fax: 603-33923799; e-mail: lsk@kossanpaint.com.my; Website: www.kossanpaint.com



PRODUCT DATA SHEET

KOSELASTEX KET-SERIES

DISCLAIMER

The information in this data sheet is provided to the best of our knowledge. However, we have no control over either quality or condition of the substrate and other factor affecting the use and application of this product. Therefore, we cannot accept any liability whatsoever or howsoever arising from the performance of the product or for any loss or damage arising from the use of this product. We reserve the right to change the product data without notice.

KOSSAN PAINT (M) SDN.BHD

1 Jalan Koporat 1/KU 9, Taman Perindustrian Meru, 42200 Kapar, Selangor D.E. Malaysia
Tel: 603-33922799; Fax: 603-33923799; e-mail: lsk@kossanpaint.com.my; Website: www.kossanpaint.com